

## Dead Load Thickness Gages 57B



XLI-57B-15

### Features

- Solid casting with ribbed frame provides strength and rigidity for accurate measurements.
- 0.003 mm/ .0001" parallelism with tables up to 19 mm/ .75" diameter.
- 283 g/ 10 oz. dead load weight for constant gaging pressure.
- 10 mm/ .407" diameter flat upper 54.0 mm/ 2.125" lower contacts.
- Indicator mounts with adjustable back for quick positioning for each gaging requirement.
- Available with Dial Indicator or Digital Electronic Indicator.
- Gage is supplied with a lift lever so work can be easily placed between the table and contact.
- Four-inch throat depth for part clearance.

### Technical Data

Metric	Order no.	Inch	Capacity	Description
57B-14M	57B-14		0-2.5 mm/ 0-.10"	Dial Indicator readout with 2.5mm/ .10" sensitive range and .002 mm/ .0001" grads.
57B-15M	57B-15		0-25 mm/ 0-1"	Dial Indicator readout with 25mm/ 1" sensitive range and .01 mm/ .001" grads.
	XLI-57B-15			μMaxμm® XL Digital Indicator with 25mm/ 1" range and .001 mm/ .00005" resolution (Model XLI-50002).

Alternate Indicators and contact points available upon request.  
Contact Mahr Federal.