



# CATALOG

## 2021/22

Status: 10.2021









**01 High pressure adhesive grease**  
High press

- ▶ Item no. 2894-445-1
- ▶ Content: 400 ml
- ▶ Quantity per box: 24
- ▶ Technical specifications
  - highly water-repellent
  - extremely pressure resistant
  - free of sticky polymer thickeners, therefore does not bind dirt
  - silicone free
  - excellent adhesive properties
  - very good creeping ability
  - Temperature resistance from - 20 ° C to 140 ° C (briefly 180 ° C)
  - Color: beige / transparent



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



**02 High pressure adhesive grease**  
High Press Protect

- ▶ Item no. 2894-445-5
- ▶ Content: 400 ml
- ▶ Quantity per box: 12



- ▶ Technical specifications
  - H1 food approval
  - extremely stable and adhesive
  - salt and hot water resistant
  - free of sticky polymer thickeners (therefore does not bind dirt)
  - silicone free
  - excellent high pressure and high temperature properties
  - flashes off quickly
  - high layer thickness
  - good creep properties
  - For all high-pressure vehicle parts such as: door hinges, gear wheels, motorcycle chains, wire ropes, chains, wire ropes, hinges, etc.
  - Temperature resistance from -20 ° C to 150 ° C
  - NSF Registration No. 151238



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



**03 Adhesive grease**  
High-Press Ultra

- ▶ Item no. 2894-445-3
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

- ▶ Technical specifications
  - lubricates all kinds of moving machine parts such as hinges, door straps, chains, gears, wire ropes, slide rails, etc.
  - extremely creeping
  - extremely adhesive
  - high pressure resistance
  - salt and hot water resistant
  - Temperature resistance from - 20 ° C to 140 ° C (briefly 180 ° C)
  - silicone free
  - Color: light blue



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2







**01 High pressure adhesive grease**  
High-Press Black

- ▶ Item no. 2894-445-2
- ▶ Content: 400 ml
- ▶ Quantity per box: 24
- ▶ Technical specifications
  - suitable for use in all technical areas
  - high penetration ability
  - excellent adhesive properties
  - water-repellent and protects against corrosion
  - best running properties at high temperatures and speeds
  - Temperature resistance from -20 ° C to 200 ° C
  - silicone free
  - Color: Black



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



**02 White grease**  
Bio-Top Protect

- ▶ Item no. 2894-446
- ▶ Content: 400 ml
- ▶ Quantity per box: 24



- ▶ Technical specifications
  - water repellent
  - good lubricating properties
  - good abrasion resistance
  - rust-releasing
  - moisture displacing
  - universally applicable
  - pressure resistant
  - extremely durable
  - very good adhesive strength
  - silicone free
  - Temperature resistance from -10 ° C to 150 ° C



**03 Fully synthetic maintenance lubricating oil spray**  
Multi Protect

- ▶ Item no. 2894-445-6
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications



- fully synthetic
- resistant to oxidation
- extremely creeping
- flex-stable
- silicone free
- salt and hot water resistant
- optimal corrosion protection properties
- good high pressure and high temperature stability
- Temperature resistance from -30 ° C to 150 ° C



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2







01  
**Multispray PTFE / ceramic oil spray**  
Teflux

- ▶ Item no. 2894-445-4
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

- ▶ Item no. 2894-445-415
- ▶ Content: 150 ml
- ▶ Quantity per box: 12

- ▶ Technical specifications
  - extremely creeping
  - water-repellent and protects against corrosion
  - high pressure resistance
  - lubricates and oils moving machine parts of all kinds such as gears, hinges, etc.
  - excellent emergency running properties thanks to PTFE and ceramic additives
  - silicone free
  - Color beige
  - Odor: vanilla



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



02  
**Maintenance spray**  
ECO

- ▶ Item no. 2897-351-2
- ▶ Content: 600 ml
- ▶ Quantity per box: 12

- ▶ Technical specifications
  - ensures reliable lubrication - even in the most remote places
  - has a friction-reducing effect
  - water repellent



03  
**Interior mounting spray**  
Soules Protect

- ▶ Item no. 2897-449-1
- ▶ Content: 300 ml
- ▶ Quantity per box: 12

- ▶ Technical specifications
  - silicone free
  - displaces moisture
  - antistatic
  - does not resinify and provides permanent protection against UV rays
  - prevents door seals from freezing on



01

**Silicone spray**  
ECO

- ▶ Item no. 2897-322-2
- ▶ Content: 600 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- reduces squeaking noises
- water repellent
- impregnating
- does not leave any stains
- temperature resistant from -50 ° C to 250 ° C

02

**Silicone spray**  
Siprem

- ▶ Item no. 2897-322
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- high quality silicone with a minimum content of 18%
- extremely water repellent
- does not leave any stains
- very high lubricating power

03

**Silicone grease spray**  
Siltron

- ▶ Item no. 2897-324
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- highly water-repellent
- lubricates and seals
- is compatible with elastomers
- does not resinify and is extremely resistant to aging
- insulates surfaces against leakage currents and flashovers, even at high and low temperatures

04

**Dry lubricant**  
TT - power

- ▶ Item no. 2897-447
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- invisible, almost imperceptible sliding film
- oil-free, grease-free, silicone-free
- prevents dust generation
- antistatic



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2







01  
**„Inspection and Maintenance“ starter set**  
 6 pieces

► Item no. 2897-000-001

- 1x Siprem Silicone Premium - silicone spray 400ml (Item 2897-322)
- 1x Teflux - PTFE / ceramic oil spray 400ml (item 2894-445-4)
- 1x Off-Shore Silver - brake protection spray 400ml (item 2894-449)
- 1x TT-Power - dry lubricant 400ml (Item 2897-447)
- 1x High-Press Ultra - high pressure adhesive lubricant 400ml (Item 2894-445-3)
- 1x Super Crack Ultra - ice spray 400ml (Item 2894-442-1)



02  
**„Protect“ starter set**  
 6 parts



► Item no. 2897-000-002

- 1x Oxim Protect - rust remover 400ml (Art. 2894-444-1)
- 1x High Press Protect - high pressure adhesive lubricant 400ml (Art. 2894-445-5)
- 1x Multi Protect - maintenance oil spray 400ML (Art. 2894-445-6)
- 1x Bio-Top white Protect - lubricating grease 400ml (Art. 2894-446)
- 1x New Look Protect - cockpit care 400ml (Art. 2897-337-1)
- 1x Anitlox Protect - welding protection 400ml (Art. 2893-908)



01  
**Multipurpose grease**  
BG-B

- ▶ Item no. 2986-02
- ▶ Content: 400 g
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
  - for drive shafts
  - mechanically highly resilient
  - acid free
  - with graphite
  - Contains solid lubricant
  - water repellent
  - anti-corrosive
  - Color: Black
  - Temperature resistance from -30 ° C to 120 ° C
  - NLGI class 2



02  
**Multipurpose grease**  
BG-Y

- ▶ Item no. 2986-021
- ▶ Content: 400 g
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
  - mechanically highly resilient
  - silicone free
  - acid free
  - flex-stable
  - resistant to oxidation
  - water repellent
  - anti-corrosive
  - NLGI class 2
  - Color yellow
  - Temperature resistance from -30 ° C to 120 ° C



03  
**Lever grease gun**

- ▶ Item no. 7986-0
  
- ▶ Technical specifications
  - M10 x 1
  - for 400g cartridges or 500g loose fat
  - Short stroke system
  - stepless piston rod fixation
  - Fill / vent valve
  - ergonomic handle, according to DIN 1283
  - TÜV, DLG, BLT tested



04  
**High pressure armored hose**  
for lever grease gun (Item No. 7986-0)

- ▶ Item no. 7986-03
  
- ▶ Technical specifications
  - M10 x 1



05  
**Hydraulic grip mouthpiece**  
for lever grease gun (Item No. 7986-0)

- ▶ Item no. 7986-04
  
- ▶ Technical specifications
  - M10 x 1
  - according to DIN 71412
  - for grease gun (7986-0)



06  
**Hydraulic safety grip mouthpiece**  
Safelock

- ▶ Item no. 7986-05
  
- ▶ Technical specifications
  - M10 x 1
  - with hardened 4-jaws made of tool steel
  - with high-performance hydraulic seal
  - with integrated linear swivel joint
  - with integrated check valve
  - Uncoupling possible up to a pressure of over 600 bar
  - no splashing away when uncoupling
  - Outside diameter according to DIN
  - Made in Germany





01

**One-hand lever grease gun**

- ▶ Item no. 7986-1
- ▶ Technical specifications
  - with galvanized steel grease container
  - ergonomically shaped lever mechanism
  - Pressure output approx. 300 bar
  - open the cartridge without tools
  - easy, fast and absolutely clean loading and removal of the grease cartridges - without opening the press
  - no venting necessary
  - optimal residual emptying of the cartridges
  - Hose length: 30cm



02

**Multipurpose grease**  
Greasal

- ▶ Item no. 2986-031
- ▶ Content: 400 g
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - smooth, brisk texture
  - soft consistency
  - acid-free, mill-stable
  - resistant to oxidation
  - rust preventive
  - Temperature resistance from -30 °C to 120 °C
  - NLGI class 2 (2K-30 according to DIN 51 502)
  - Screw cartridge (Lube Shuttle system cartridges)



03

**Cartridge adapter TG**  
LS 500

- ▶ Item no. 7986-2
- ▶ Technical specifications
  - Use: with our one-hand lever grease gun Art. No. 7986-1
  - for dispensing 500ml Lube Shuttle grease cartridges with screw thread (large thread)




04

**Starter set**  
Lubricating greases

- ▶ Item no. 2897-000-005
  - 1 x 400ml high pressure adhesive lubricant High Press (Item No. 2894-445-1)
  - 1 x 400ml high pressure adhesive lubricant High Press black (Art.-No. 2894-445-2)
  - 1 x 400ml high pressure adhesive lubricant High Press ultra (Art.-No. 2894-445-3)
  - 1 x 400ml high pressure adhesive lubricant High Press Protect (Art.No. 2894-445-5)
  - 1 x 400ml lubricating grease white Bio-Top Protect (Item No. 2894-446)
  - 1 x 400ml Siltron silicone grease (item no. 2897-324)







01

**Rust remover**  
Oxime

- ▶ Item no. 2894-441-1
- ▶ Content: 5 litres

- ▶ Technical specifications
- loosens stuck, rusted screw connections
- works quickly and effectively
- very high lubricating properties
- moisturizing
- displacing water
- prevents further rust formation
- Temperature range: -20 ° C to 250 ° C

- ▶ Item no. 2000-000-005
- ▶ Pouring tap
- ▶ for 5 liter containers



02

**Rust remover spray**  
Oxime Ultra

- ▶ Item no. 2894-444
- ▶ Content: 400 ml
- ▶ Quantity per box: 24

- ▶ Technical specifications
- very high lubricating properties
- has a moisturizing effect
- displacing water
- preventive against further rusting
- Temperature resistance from -20 ° C to 250 ° C



**Replacement spray head**  
with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2



03

**Rust remover**  
Oxime Protect

- ▶ Item no. 2894-444-1
- ▶ Content: 400 ml
- ▶ Quantity per box: 24



- ▶ Technical specifications
- use against rust, squeaking and creaking noises
- prevents further rusting
- Temperature resistance from -20 ° C to 250 ° C







01  
**Ice rust remover**  
Super crack ultra

- ▶ Item no. 2894-442-1
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - very good creeping ability
  - highly effective corrosion protection
  - permanently water-repellent
  - guarantees an extreme relubrication effect
  - very icy, cools down to -40 ° C
  - High-performance release agent with silver-colored aluminum particles



02  
**Kraft Multi rust remover with cold shock effect**  
Multi crack

- ▶ Item no. 2894-500
- ▶ Content: 250 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - extremely rust-releasing properties
  - long-lasting effect
  - absolutely free of mineral oil
  - very good creeping ability
  - Cold shock effect down to -40 ° C
  - effective quickly
  - unique active ingredient formula
  - Multifunctional spray head for point and area jets
  - silicone free
  - Transport lock on the back of the spray head



03  
**Injector, glow plug and spark plug remover**  
Inject crack

- ▶ Item no. 2894-440
- ▶ Content: 250 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - removes incrustations and oil residues
  - up to 50% lower creep effect than e.g. a standard rust remover
  - free from mineral oils, acids and silicones
  - very economical in use due to the high proportion of active ingredients



01

**Brake cleaner**

Bremtec

- ▶ Item no. 2897-333-600
- ▶ Content: 600 ml
- ▶ Quantity per box: 24
  
- ▶ Item no. 2897-333-5
- ▶ Content: 5 litres
- ▶ PU: 1
  
- ▶ Item no. 2897-333-31
- ▶ Content: 30 litres
- ▶ PU: 1
  
- ▶ Technical specifications
- containing acetone
- has a degreasing effect



**Pouring tap**

- ▶ Item no. 2000-000-005
- ▶ PU: 1
- ▶ for 5 liter containers
  
- ▶ Item no. 2000-000-030
- ▶ PU: 1
- ▶ for 30 liter containers



**R3 / 4 "metal pouring tap**

- ▶ Item no. 2000-000-062
- ▶ PU: 1
- ▶ Discharge tap for 60 litre container



**Closure adapter for metal pouring tap**

- ▶ Item no. 2000-000-061
- ▶ PU: 1
- ▶ Adapter for 30 and 60 litre containers



02

**Pressure pump spray bottle**  
for acidic liquids

- ▶ Item no. 2897-333-100
  
- ▶ Technical specifications
- Operating pressure 3 bar
- unfilled
- Capacity 1 liter
- Labels available separately for better recognition

**Replacement seal**

- ▶ Item no. 2897-333-101

**Application bottle label**  
for Bremtec brake cleaner

- ▶ Item no. 1960-000-1



03

**Compressed air spray bottle**  
refillable

- ▶ Item no. 2897-900
- ▶ Content: Aquano
- ▶ PU: 1
  
- ▶ Technical specifications
- Suitable for all liquid materials that can be worked using compressed air



**Headboard complete**

- ▶ Item no. 2897-900-15
- ▶ PU: 1



**Spray head jet**

- ▶ Item no. 2897-900-12
- ▶ PU: 1



**Spray head vortex**

- ▶ Item no. 2897-900-13
- ▶ PU: 1

**Riser pipe**

- ▶ Item no. 2897-900-16
- ▶ PU: 5



**O-ring**

- ▶ Item no. 2897-900-11
- ▶ PU: 1



**Union nut**

- ▶ Item no. 2897-900-10
- ▶ PU: 1







01

**Brake cleaner**

MC-1

- ▶ Item no. 2897-333-500
- ▶ Content: 500 ml
- ▶ Quantity per box: 30
- ▶ Technical specifications
  - acetone-free quality cleaner
  - very effectively removes oil, dirt, brake fluid and lining abrasion from disc brakes, brake pads and linings as well as many other vehicle parts
  - washes out impurities and deposits
  - removes oil, grease, dust and resin residues, brake fluid and lining wear from disc brakes
  - Thanks to careful lubrication, the service life of the machined components is increased



02

**Brake cleaner, safety cleaner**

Bremtec Safe

- ▶ Item no. 2897-333-700
- ▶ Content: 500 ml
- ▶ Quantity per box: 12
- ▶ Item no. 2897-333-730
- ▶ Content: 30 litre
- ▶ PU: 1
- ▶ Technical specifications
  - flame retardant propellant
  - lower explosion limit > 1.5% vol.
  - Recommended product according to the Ordinance on Hazardous Substances (protection level 2)
  - 25% naphtha colorless

**Pouring tap**

for 30 liter containers

- ▶ Item no. 2000-000-030
- ▶ PU: 1



03

**Pressure pump spray bottle**

for Bremtec Safe

- ▶ Item no. 2897-333-170
- ▶ Technical specifications
  - Operating pressure 3 bar
  - unfilled
  - Capacity 1 liter
  - Labels available separately for better recognition
  - including a replacement seal set (Item No. 2897-333-171)
- For filling with the following Normfest product:
  - Bremtec Safe brake cleaner

**Replacement seal**  
for Bremtec Safe bottle

- ▶ Item no. 2897-333-171
- ▶ PU: 1





01

**Copper fat paste**  
COP

- ▶ Item no. 2894-451-1
- ▶ Content: 250 g can
- ▶ Quantity per box: 5
  
- ▶ Item no. 2894-450
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
  
- ▶ **Technical specifications**
- high pressure resistant
- temperature resistant up to 1,200 ° C
- anti-corrosive
- water resistant
- extremely adhesive
- resistant to oxidation
- silicone free
- do not apply to friction surfaces
- NOT RECOMMENDED FOR ABS VEHICLES



03

**High-performance brake and assembly spray**  
500ml

- ▶ Item no. 2894-452
- ▶ Content: Aquano
- ▶ Quantity per box: 6
  
- ▶ **Technical specifications**
- for extremely temperature and pressure loaded sliding surfaces
- Excellent lubricating effect over a wide temperature range from -30 ° C to 1,350 ° C
- wide range of uses and high long-term effect
- very good adhesion to almost all surfaces
- non-conductive
- extremely resistant to water, alkalis, diluted acids and corrosion
- effectively prevents brake parts or the like from sticking.
- Allows easy dismantling even of hot screws on screw connections subject to high temperatures



04

**Brake protection spray**  
Off-shore silver

- ▶ Item no. 2894-449
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
  
- ▶ **Technical specifications**
- Sweat, splash and salt water resistant
- very good and lasting lubricating effect
- long-term corrosion protection
- is particularly suitable for vehicles with ABS braking systems
- Temperature resistance up to 1,400 ° C
- metal free
- prevents corrosion and squeaking noises
- silicone free
- Cold flow properties guarantee that the product remains in place at all times



05

**Brake protection paste**  
Off-shore silver

- ▶ Item no. 2894-449-200
- ▶ Content: 200 g
- ▶ Quantity per box: 12
  
- ▶ **Technical specifications**
- Sweat, splash and salt water resistant
- very good and lasting lubricating effect
- long-term corrosion protection
- is particularly suitable for vehicles with ABS braking systems
- temperature resistant up to 1,400 ° C
- silicone free



**Replacement brush for off-shore**  
with protective cover

- ▶ Item no. 2894-448-201
- ▶ PU: 1





01  
**brake fluid**  
DOT4

- ▶ Item no. 2894-410
- ▶ Content: 5 litres
- ▶ PU: 1
  
- ▶ Item no. 2894-410-30
- ▶ Content: 30 litre
- ▶ PU: 1
  
- ▶ Technical specifications
- Wet boiling point above 160 ° C
- Boiling point over 250 ° C



02  
**brake fluid**  
DOT4 Plus

- ▶ Item no. 2894-415
- ▶ Content: 5 litres
- ▶ PU: 1
  
- ▶ Item no. 2894-415-30
- ▶ Content: 30 litre
- ▶ PU: 1
  
- ▶ Technical specifications
- suitable for all hydraulic brake systems with synthetic fluid
- Wet boiling point above 180 ° C
- Boiling point over 260 ° C



**Pouring tap**

- ▶ Item no. 2000-000-005
- ▶ PU: 1
- ▶ for 5 liter containers
  
- ▶ Item no. 2000-000-030
- ▶ PU: 1
- ▶ for 30 liter containers



**Tester**  
for brake fluids

- ▶ Item no. 8715-999-50
- ▶ PU: 1
- ▶ Replacement battery 3722-24



03  
**High performance brake fluid**  
DOT 4 LV high performance

- ▶ Item no. 2894-435
- ▶ Content: 5 litres
- ▶ PU: 1
  
- ▶ Item no. 2894-430
- ▶ Content: 30 litres
- ▶ PU: 1
  
- ▶ Technical specifications
- especially with Ford approval
- suitable for all hydraulic brake systems with synthetic fluid
- miscible with brake fluids of the same specification
- neutral behavior towards brake parts
- increased safety through reduced boiling point drop
- corresponds to DOT-4 FMVSS 116 and SAEJ 1703
- Boiling point over 265 ° C
- Wet boiling point above 175 ° C



01

**Airpress filling station**

- ▶ Item no. 2897-910-100
- ▶ Technical specifications
- universal use in many industrial sectors
- there is no need to buy any spray
- no disposal costs
- no environmental pollution from the use of air as a propellant



02

**Airspray pressure bottle for Bremtec A2**

- ▶ Item no. 2897-910-1
- ▶ Content: 400 ml
- ▶ PU: 1



03

**Airspray pressure bottle for Bremtec**

- ▶ Item no. 2897-910-2
- ▶ Content: 400 ml
- ▶ PU: 1



04

**Airspray pressure bottle for oxime**

- ▶ Item no. 2897-910-3
- ▶ Content: 400 ml
- ▶ PU: 1



**Material air valve**

- ▶ Item no. 2897-910-103
- ▶ PU: 1



**Air valve**

- ▶ Item no. 2897-910-104
- ▶ PU: 1



**Seal holder with groove ring**

- ▶ Item no. 2897-910-105
- ▶ PU: 1




**Plug nipple with external thread 1/4 "**

- ▶ Item no. 8699-25-531
- ▶ PU: 1



**Spare part material / air**

- ▶ Item no. 2897-910-106
- ▶ PU: 1



**Seal kit for the Air Press filling station**

- ▶ Item no. 2897-910-107
- ▶ PU: 1



**Barrel connection including accessories for 60 liters**

- ▶ Item no. 2897-910-110
- ▶ PU: 1



**Valve with riser pipe**

- ▶ Item no. 2897-910-101
- ▶ PU: 1



**Spray head with round jet**

- ▶ Item no. 2897-910-102
- ▶ PU: 1



**Spray head with point jet**

- ▶ Item no. 2897-910-108
- ▶ PU: 1





01

**silicone**

Silon Black

- ▶ Item no. 2896-640-2
- ▶ Content: 200 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- hardens to a hard, rubber-like mass with practically no shrinkage (<3%) as soon as it is exposed to air humidity
- adheres to metal, glass, painted surfaces, ceramics and most plastic surfaces
- resistant to weather conditions, vibrations, moisture
- temperature resistant from -50 ° C to 230 ° C

**Replacement pistol grip**

for Silon

- ▶ Item no. 2896-640-3
- ▶ PU: 1



02

**silicone**

Silon Red

- ▶ Item no. 2896-640-1
- ▶ Content: 200 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- hardens to a hard, rubber-like mass with practically no shrinkage (<3%) as soon as it is exposed to air humidity
- adheres to metal, glass, painted surfaces, ceramics and most plastic surfaces
- resistant to weather conditions, vibrations, moisture
- temperature resistant from -50 ° C to 300 ° C

**Replacement pistol grip**

for Silon

- ▶ Item no. 2896-640-3
- ▶ PU: 1



03

**Seal remover**

Seal-Ex

- ▶ Item no. 2896-663
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

▶ Technical specifications

- applicable to objects made of metal, wood, ceramic, glass, polyethylene, polypropylene
- do not use on sensitive plastics such as PVC, linoleum and synthetic





**01**  
**Surface seal**  
green

- ▶ Item no. 2896-520
- ▶ Content: 50 g
- ▶ PU: 1
  
- ▶ **Technical specifications**
- max.gap filling capacity: 0.3 mm
- hand-tight in 20-40 min.
- functional in 1-3 hours
- Temperature resistance from -55 °C to 150 °C
- Resistant to water, mineral oils, synthetic lubricants, fuels, organic solvents and coolants

**02**  
**Surface seal**  
orange

- ▶ Item no. 2896-521
- ▶ Content: 50 g
- ▶ PU: 1
  
- ▶ **Technical specifications**
- max.gap filling capacity: 0.5 mm
- hand-tight in 15-30 min.
- functional in 1-3 hours
- Temperature resistance from -55 °C to 150 °C
- Resistant to water, mineral oils, synthetic lubricants, fuels, organic solvents and coolants



**03**  
**Pipe thread seal**

- ▶ Item no. 2896-550-51
- ▶ Content: 50 ml
- ▶ PU: 1
  
- ▶ **Technical specifications**
- replaces hemp, PTFE and solid sealant
- Parts can be readjusted after joining
- high quality waterproofing
- additional protection against corrosion
- 
- max.gap filling capacity: 0.50 mm
- max.thread: (metr) M80
- hand-tight in 15-30 min.
- functional in 1-3 hours
- Skill class (DIN 30661): 2
- Temperature resistance from -55 °C to 150 °C
- Resistant to petrol, diesel, water, water-glycol mixtures, mineral oils, hydraulic fluids
- Exception: acids and alkalis in high concentration as well as methylene chloride



**04**  
**Bushing and bearing mounting**

- ▶ Item no. 2896-540
- ▶ Content: 24 ml
- ▶ PU: 1
  
- ▶ **Technical specifications**
- Skill class (DIN 30661): 55-70
- max.gap filling capacity: 0.15 mm
- max.thread: (metr) M20
- Temperature resistance from -55 °C to 175 °C
- hand-tight in 2-5 min.
- functional in 1-3 hours



**05**  
**Permanently plastic universal seal**  
Plastomar

- ▶ Item no. 2896-502
- ▶ Content: 85 g
- ▶ Quantity per box: 10
  
- ▶ **Technical specifications**
- Maximum splitting capacity of 0.2 mm
- temperature resistant from -55 °C to 270 °C
- Let it flash off for 10 minutes
- silicone free
- with dosing nozzle
- Red color







**01**  
**Screw locking**  
medium strength

- ▶ Item no. 2896-531-50
- ▶ Content: 50 ml
- ▶ Quantity per box: 10
  
- ▶ Technical specifications
- max.gap filling capacity: 0.25 mm
- max.thread (metric) M36
- hand-tight in 10-20 min.
- functional in 1-3 hours
- medium strength, strength class? (DIN 30661)
- temperature resistant from -55 ° C to 150 ° C

**02**  
**Screw locking**  
extra strength

- ▶ Item no. 2896-530-50
- ▶ Content: 50 ml
- ▶ Quantity per box: 10
  
- ▶ Technical specifications
- max.gap filling capacity: 0.15 mm
- max.thread (metric) M20
- hand-tight in 10-20 min.
- functional in 1-3 hours
- high strength, skill class (DIN 30661)
- temperature resistant from -55 ° C to 150 ° C



**03**  
**Engine tight**  
Mot Seal

- ▶ Item no. 2897-374
- ▶ Content: 300 ml
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
- prevents blue-smoking exhausts
- regenerates engine seals made of plastic and rubber
- prevents pollution from oil dripping engines



**04**  
**Engine oil circuit cleaner**  
Mot Clean

- ▶ Item no. 2897-375
- ▶ Content: 500 ml
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
- gentle and quick cleaning
- neutral to seals and other materials built into the engine
- High profitability
- simple application





01

**Radiator tight**

Wheel seal

- ▶ Item no. 2897-372
- ▶ Content: 150 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- permanently and reliably seals hairline cracks and small leaks
- Compatible with antifreeze agents and coolants, neutral against rubber, plastics, light and non-ferrous metals
- no negative side effects on the water pump and heating circuit
- suitable for closed cooling systems
- suitable for aluminum coolers
- also suitable for preventive use

02

**Radiator cleaner**

Wheel clean

- ▶ Item no. 2897-373
- ▶ Content: 250 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- chemical calcium conversion
- Removal of fat, limescale and oil
- Sludge dispersion
- neutral to the radiator materials used
- rubber and plastic compatible
- Compatible with frost protection
- does not contain any aggressive acids or alkalis
- one can is sufficient for a quantity of up to 10 liters of cooling water



03

**Diesel additive**

CT 60

- ▶ Item no. 2897-370
- ▶ Content: 300 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- ensures cleanliness and prevents deposits in the fuel system and combustion chamber
- keeps the injection nozzles clean, ensures better engine combustion, which leads to lower specific fuel consumption and maximum engine performance
- prevents the injection nozzles from sticking and gumming up
- increases the lubricating effect of low-sulfur diesel fuels and protects the distributor injection pumps from wear
- compatible with all modern diesel oxidation catalysts



04

**Gasoline additive**

OT 100

- ▶ Item no. 2897-371
- ▶ Content: 300 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- suitable for all gasoline injection systems
- cleans the injection system of fuel residues
- removes coking and deposits from flow dividers, injection valves, inlet valves and other components of the fuel system
- ensures optimal driving behavior and low fuel consumption through precise injection metering and atomization
- guarantees low levels of pollutants in the exhaust gas





01  
**Diesel intake system cleaner**  
DC980

- ▶ Item no. 2897-369
- ▶ Content: 400 ml
- ▶ Quantity per box: 8
  
- ▶ Technical specifications
  - Special cleaner with CO2 propellant
  - simple and targeted application
  - colorless and residue-free
  - powerful loosening power
  - over 95% active ingredient

02  
**Diesel soot particle filter cleaner**  
DPF100

- ▶ Item no. 2897-380
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
  - Dissolves carbon deposits excellently
  - not flammable
  - Can be cleaned without dismantling the? Particle filter
  - to restore the full? absorption capacity of the diesel particulate filter

03  
**Throttle valve cleaner**  
VC 980

- ▶ Item no. 2897-368
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
  - cleans the carburetor inside and out
  - flushes holes and nozzles
  - for cleaning components in the intake area
  - EGR valve (exhaust gas recirculation valve)

04  
**Marten repellent spray**  
Wild Guard

- ▶ Item no. 2897-329
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
  
- ▶ Technical specifications
  - Helps to effectively deter martens
  - Double-effect means that electric cables, ignition cables, brake and coolant tubes, sleeves and fan belts are protected from marten bites
  - Reapplied after every engine and underbody wash

**Processing hose**

long, with spray head

- ▶ Item no. 2897-368-1
- ▶ PU: 1







01  
**Electrical contact cleaner**  
TermClean

- ▶ Item no. 2897-334
- ▶ Content: 400 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - Cleaning of all contacts
  - enables greasy dirt to be removed and loosens old incrustations
  - Safe to use with electrical and mechanical office machines, computers, cash registers, radio and television sets
  - including brush attachment?
  - The product is not suitable for use on parts that are in operation!



02  
**Contact helper**  
Contact

- ▶ Item no. 2897-331
- ▶ Content: 300 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - displaces moisture
  - improves electrical conductivity
  - silicone free



03  
**Battery pole protection spray**  
Poltec

- ▶ Item no. 2897-332-300
- ▶ Content: 300 ml
- ▶ Quantity per box: 12
- ▶ Technical specifications
  - insulates bare sheet metal and electrical connections against corrosion from environmental influences (salts, water, acids and alkalis, moisture, etc.)
  - weatherproof
  - resistant to oxidation
  - anti-corrosive
  - moisture repellent
  - prevents contact resistance and voltage drop
  - Temperature resistance from -30 °C to 130 °C
  - silicone free



04  
**Acid testers**  
for battery

- ▶ Item no. 8853-600-2
- ▶ PU: 1
- ▶ Technical specifications
  - easy to use
  - Clear scaling with three result areas
  - red (cell discharged)
  - yellow (cell satisfactory condition)
  - green (cell in good condition)





01

**Leak detector**

Spy Plus

- ▶ Item no. 2896-661
- ▶ Content: 400 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- meets the requirements of DIN EN 14291
- non-flammable - leak detection also possible with flammable gases
- suitable for all technical gases in compressed air, compressed gas and air conditioning systems, compressors, welding equipment, compressed air braking systems, tires, hoses or transport tanks
- no stress corrosion cracking in plastics such as PVC or PE
- Temperature application range: -15 ° C to 50 ° C
- not corrosive

02

**Leak detector spray**

Spy Dry

- ▶ Item no. 2896-662-500
- ▶ Content: Aquano
- ▶ Quantity per box: 12

▶ **Technical specifications**

- to find leaks from which oil, gasoline or other liquids are leaking
- free of grease and silicone
- based on marble powder

03

**Icing spray**

Arctic

- ▶ Item no. 2897-325
- ▶ Content: 200 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- Construction parts made of metal such as ball bearings, bushings, chain links, shafts, etc. can be inserted into the tightest of fits
- Faults in electrical circuits (due to thermal overload) can be easily found by local cooling
- removes dirt such as chocolate or chewing gum from upholstery

04

**Jump start spray**

Super start plus

- ▶ Item no. 2897-330-310
- ▶ Content: 300 ml
- ▶ Quantity per box: 12

▶ **Technical specifications**

- very high ignition properties
- enables a cold start even at extremely low temperatures
- improves starting behavior in wet conditions
- suitable for 2-stroke and 4-stroke petrol engines
- Also suitable for diesel engines (note the application note on the product: „Start diesel engines at full throttle and do not preheat!“)

**Replacement spray head**

with capillary tube

- ▶ Item no. 2897-300-140
- ▶ PU: 2





01

**Glass cleaner**  
Stries Protect

- ▶ Item no. 2897-340
- ▶ Inhalt: Aquano
- ▶ Quantity per box: 12
  
- ▶ Item no. 2897-340-5
- ▶ Inhalt: Uni-Star
- ▶ PU: 1

- ▶ Item no. 2897-340-30
- ▶ Inhalt: 30 liters
- ▶ PU: 1

- ▶ **Technical specifications**
- Leaves behind clear, shiny, streak-free and clean glass surfaces
- removes dirt, stains, fingerprints, grease, nicotine, flies, etc.
- can be used on glass and polycarbonate glass
- silicone and ammonia free
- has no abrasives

**Pouring tap**

- ▶ Item no. 2000-000-005
- ▶ for 5 liter containers
- ▶ PU: 1

- ▶ Item no. 2000-000-030
- ▶ for 30 litre container
- ▶ PU: 1



02

**High-tech special cleaner**  
Terpanol Power

- ▶ Item no. 2897-323
- ▶ Inhalt: Starter Set
- ▶ Quantity per box: 12

- ▶ **Technical specifications**
- contains orange terpenes from 100% renewable raw materials
- optimally removes adhesive residues, oils, fats, waxes, waterproof edging traces, graffiti
- stronger loosening force of the respective dirt
- Dissolve after a very short time (approx. 20 seconds)



03

**Interior intensive cleaner**  
Interno Protect

- ▶ Item no. 2000-05
- ▶ Content: 500 ml
- ▶ Quantity per box: 12

- ▶ Item no. 2000-05-5
- ▶ Inhalt: 5 litres
- ▶ PU: 1

- ▶ **Technical specifications**
- cares for hard and soft surfaces such as plastic, vinyl, chrome, sealing and door sill trims, car leather, upholstery and carpets
- Leaves a matt finish and a pleasantly fresh scent on plastic surfaces
- acid and silicone free
- does not contain hydrocarbon solvents
- not suitable for suede and alcantara
- ready to use



**Pouring tap**

- ▶ Item no. 2000-000-005
- ▶ for 5 liter containers
- ▶ PU: 1





03

**Lightning deicer**

Blizzard Ultra

- ▶ Item no. 2897-231
- ▶ Content: 500 ml
- ▶ Quantity per box: 6



- ▶ Technical specifications
- removes ice from icy car windows in a flash
- does not leave any streaks
- laborious scratching is no longer necessary

01

**Antifreeze for windscreen washer system**

Frostex

- ▶ Item no. 2897-314
- ▶ Content: 1000 ml
- ▶ Quantity per box: 12

- ▶ Item no. 2897-315
- ▶ Content: Uni-Star
- ▶ PU: 1

- ▶ Item no. 2897-318
- ▶ Content: 30 litre
- ▶ PU: 1

- ▶ Technical specifications
- methanol free
- undiluted, frost-proof down to -70 ° C
- suitable for fan nozzles and polycarbonate glasses



**Pouring tap**

- ▶ Item no. 2000-000-005
  - ▶ PU: 1
  - ▶ for 5 liter containers
- ▶ Item no. 2000-000-030
  - ▶ PU: 1
  - ▶ for 30 liter containers







**01 Frost protection tester**  
for cooling water

- ▶ Item no. 8853-600-1
- ▶ Technical specifications
  - Technically modern construction that has been tried and tested many times around the world
  - easy, quick and accurate measurement
  - stable plastic housing
  - Hanging loop
  - Pendulum pointer - no vertical position of the device required
  - automatic temperature compensation
  - Closure by rotary valve
  - no dripping, no drawing in of air
  - very long service life and measurement accuracy thanks to the mounting of the measuring disc and the pendulum pointer on a steel axle thus little influence from coolant contamination



**02 Frost protection tester**  
for the windscreen washer

- ▶ Item no. 8853-600-3
- ▶ Technical specifications
  - for isopropanol / methanol-water mixtures according to commercially available antifreeze for windscreen washer systems
  - with bulged plastic cylinder and glass areometer
  - Display range from 0 ° to -30 ° C with colored fields



**03 Washer concentrate**  
Summer goods

- ▶ Item no. 2897-313-30
- ▶ Content: 25 x 30 ml
- ▶ Item no. 2897-313-5
- ▶ Content: 5 litres
- ▶ PU: 1



- ▶ Technical specifications
  - Concentrate 1: 100
  - quickly and reliably removes stubborn dirt such as insects, oily films and waxes
  - Streak-free cleaning avoids dangerous stray light effects
  - does not create stress cracks in plastic headlights
  - Fan nozzles and polycarbonate glass suitable



**Dosing pump**  
for 5 liter containers

- ▶ Item no. 2897-313-509
- ▶ PU: 1
- ▶ Technical specifications
  - 1 stroke (2.5 ml)

