

Mahr Marsurt M 310

Mahr | A passion for detail

Edition 2024

Spring Sale

Mobile roughness measurement with the MarSurf M 310

- Intuitive and easy to operate like a smartphone
- Immediate measuring success thanks to program start via barcode scanner
- Uncomplicated digital connection to QM systems

Special offer prices April 1 - May 31, 2024

Comprehensive product range with Integrated Wireless

Mahr offers a comprehensive range of measuring instruments with integrated wireless data transmission for use in all areas of industrial manufacturing and quality control. The Integrated Wireless range from Mahr delivers accurate measuring results with full mobility. Modern, simple measuring solutions – without the limitations of wired technology.

MarCal 16 EWRi **Digital calipers** Micromar 40 EWRi Digital outside micrometers MarCator 1086 Ri MarCator 1086 Ri with stand **Digital indicators** Digital indicators MarCator 1086 Ri with 3-point pistol **Digital indicator** MarCator 1087 Ri with SM 60 **Digital indicator** Millimess 2001 Wi Digital Mahr comparator

Detailed information on the products can be found at https://metrology.mahr.com/en-int/ All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in NOK plus VAT are valid from April 1, 2024 to May 31, 2024

Precimar SM 60

Product groups

Products

MarCal 16 EWRi / 30 EWRi

Digital calipers with wireless interface



Micromar 40 EWRi Micrometers according to your wishes



40 EWRi-V Set 4157150

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4157100	40 EWRi	0-25	0.001	Standard version	- 5,930 -	3,850
4157101	40 EWRi	25 - 50	0.001	Standard version	<u> 6,970 </u>	4,550
4157115	40 EWRi	0-100	0.001	Standard version. set with 4 micrometers	31,300	19,900
4157120	40 EWRi-L	0-25	0.001	QUICK DRIVE, 5 mm per rotation	7,390	4,800
4157121	40 EWRi-L	25 - 50	0.001	QUICK DRIVE, 5 mm per rotation		5,500
4157150	40 EWRi-V		0.001	Universal micrometer (QUICK DRIVE) incl. measuring anvils	- 19,250 -	13,900
Accessories	s for measur	ing instruments witl	h Integrated V	Vireless		

4102220 i-Stick Wireless receiver for measuring instruments with integrated wireless

-2,190-

1,330

MarCator 1086 Ri / 1087 Ri

Practically suited to your measuring tasks



Millimess | Inductive dial comparators

Millimess 2000 Wi / 2001 Wi

see also page 14



Order no.	Product N	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4337624	1086 Ri	12.5	0.0005	Practical functions for static measurement tasks	- 8,100 -	5,700
4337625	1086 Ri	25	0.0005	Practical functions for static measurement tasks	9,160	6,500
4337663	1087 Ri	12.5	0.0005	Practical functions for static and dynamic measurement tasks	9,500	6,600
4337665	1087 Ri	25	0.0005	Practical functions for static and dynamic measurement tasks	-10,770 -	7,500
4346701	2000 Wi	± 1	0.0001	Highest sensitivity and accuracy, for static measuring tasks	-13,370 -	8,700
4346801	2001 Wi	±1	0.0001	Highest sensitivity and accuracy, for static and dynamic measuring tasks	-15,060-	9,800
Accessorie	s for meas	uring instruments	with Integrate	5		

4102220 i-Stick Wireless receiver for measuring instruments with integrated wireless

2,190 1,330

MarCal 16 ER / 16 EWR

Digital calipers without data output





Order no.	Product	Measuring range	Resolution	Depth rod	Details	List price	Offer price
		mm	mm			NOK	NOK
4103010	16 ER	0-150	0.01	round	Lapped guideway	-1 ;7 90-	1,290
4103012	16 ER	0-150	0.01	square	Lapped guideway	-1 ;7 90 -	1,290
4103205	16 ER	0-200	0.01	square	Lapped guideway	-3 ,4 20	2,400
4103300KAL	16 EWR	0-150	0.01	round	Protection class IP 67	-2 ,45 0	1,690
4103302KAL	16 EWR	0-150	0.01	square	Protection class IP 67	-2;450-	1,690
4103304KAL	16 EWR	0 - 200	0.01	square	Protection class IP 67	-3;430-	2,600

MarCal 30 EWR Digital depth gages



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4126651	30 EWR	0-150	0.01	Protection class IP67	7,080	4,800
4126652	30 EWR	0-200	0.01	Protection class IP67	8,230	5,600
4126653	30 EWR	0-300	0.01	Protection class IP67	9,350	6,500

MarCal Vernier calipers

MarCal 16 FN Pocket calipers



Order no.	Product	Measuring range	Vernier value	Depth rod	List price	Offer price
		mm	mm/inch		NOK	NOK
4100400	16 FN	0-150	0.05/1/128"	square	- 650 -	400
4100401	16 FN	0 - 200	0.05/1/128"	square	-1,690 -	1,100

Micromar 40 ER / 40 EWR

The insensitive ones for production and workshop



4157050

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4157010	40 ER	0-25	0.001	Protection class IP40	3,370 -	2,200
4157011	40 EWR	0-25	0.001	Protection class IP65	4,200	2,730
4157012	40 EWR	25 - 50	0.001	Protection class IP65	5,800	3,780
4157020	40 EWR-L	0 - 25	0.001	IP65, data output, QUICK DRIVE, 5 mm per rotation	7,180 -	4,600
4157021	40 EWR-L	25 - 50	0.001	IP65, data output, QUICK DRIVE, 5 mm per rotation		5,300
4157050	40 EWR-V	0-25	0.001	IP65, data output, universal micrometer QUICK DRIVE in a set	-20,880-	13,600

Micromar 40 A / 40 SA / 40 AS Basics for production and workshop



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4134000	40 A	0-25	0.01	Glare-free matt chrome-plated display parts	1,150	750
4134001	40 A	25 - 50	0.01	Glare-free matt chrome-plated display parts	1,780	1,150
4134050	40 SA/SET	0-100	0.01	Set of 4 micrometers	6,650	4,350
4190350	44 AS/SET	6 - 12	0.001	incl. setting rings 8 mm, 10 mm	22,280	14,500
4190351	44 AS/SET	12 - 20	0.001	incl. setting ring 16 mm	- 17,060 -	10,900
4190352	44 AS/SET	20 - 50	0.005	incl. setting rings 25 mm, 40 mm	- 38,600 -	24,900
4190353	44 AS/SET	50 - 100	0.005	incl. setting rings 60 mm, 85 mm	45,890	29,900

Micromar 44 EWR / 844 AS

Digital 3-point internal measuring devices –

precision is guaranteed



4191162

Measure holes



Order no. Product Measuring range Resolution Details List price Offer price NOK NOK mm mm 4191160 44 EWR/SET 6-12 0.001 incl. setting rings 8 mm, 10 mm 23,800 36,590 4191161 44 EWR/SET 12-20 0.001 incl. setting ring 16 mm 31,850 20,700 4191162 44 EWR/SET 20 - 50 0.001 incl. setting rings 25 mm, 40 mm 49,300 32,000 4191163 44 EWR/SET 50 - 100 0.001 incl. setting rings 60 mm, 85 mm 59,100 38,400 844 AS/SET 0.0005 incl. digital indicator 1086 R and setting rings 8 mm, 4487760 6 - 12 38,870 25,250 10 mm 34,750 4487761 844 AS/SET 12 - 20 0.0005 incl. digital indicator 1086 R and setting rings 16 mm 22,600 4487762 844 AS/SET incl. digital indicator 1086 R and setting rings 25 mm, 50,980 20 - 50 0.0005 33,150 40 mm 4487763 844 AS/SET 50 - 100 0.0005 incl. digital indicator 1086 R and setting rings 60 mm, 61,850 39,900 85 mm

MarTest 800 S / 800 SG / 800 SM

Highly sensitive measuring



Order no.	Product	Measuring range	Graduation value	Details	List price	Offer price
		mm	mm		NOK	NOK
4305200	800 S	± 0.4	0.01	Dial ø 28 mm, measuring insert length 14.5 mm	-1,690 -	1,190
4307200	800 SG	± 0.4	0.01	Dial ø 38 mm, measuring insert length 14.5 mm		1,190
4308150	800 SM	± 0.1	0.002	Dial ø 28 mm, measuring insert length 14.5 mm	2,200	1,550
4308200	800 SGM	± 0.1	0.002	Dial ø 38 mm, measuring insert length 14.5 mm	2,430	1,690
4306200	800 SL	± 0.25	0.01	Dial ø 28 mm, measuring insert length 41.24 mm	-2,730 -	1,890
4311050	810 A	10	0.01	High-contrast dial face	940	560

MarCator 1075 R / 1086 R / 1087 R Practically suited to your measuring tasks



MarCator 1086 R-HR / 1087 R-HR

Highest precision with a large measuring range



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4336010	1075 R	12.5	0.01	Basic functions for static measuring tasks	3,400	1,990
4336020	1075 R	12.5	0.005	Basic functions for static measuring tasks	4,080	2,800
4336030	1075 R	12.5	0.001	Basic functions for static measuring tasks	- 6,090 -	3,900
4337130	1086 R	12.5	0.01	Practical functions for static measurement tasks	- 5,680 -	3,920
4337620	1086 R	12.5	0.0005	Practical functions for static measurement tasks	- 6,870 -	4,830
4337621	1086 R	25	0.0005	Practical functions for static measurement tasks	- 8,380 -	5,900
4337660	1087 R	12.5	0.0005	Practical functions for static and dynamic measurement tasks	8,820	5,900
4337661	1087 R	25	0.0005	Practical functions for static and dynamic measurement tasks	- 10,130 -	6,900
4337697	1086 R-HR	12.5	0.0001	High-resolution, practical functions for static measurement tasks		7,400
4337695	1087 R-HR	12.5	0.0001	High-resolution, practical functions for static and dynamic measurement tasks	- 12,470 -	8,700

Highest level of precision

Integrated Wireless

 Integrated Wireless interface
 Sending and receiving measuring data and various parameters



Lock individual keys and functions Remote-controlled settings can be conFigureed easily using MarCom Professional Software



First digital comparator indicator with touch operation

Extensive advantages:

- Keys react even with the slightest touch
- This prevents a measuring device from being adjusted or deformed – maximum measuring certainty

Hardened glass front

- Scratch and impact-resistant surface
- Excellent protection against scratches and penetrating liquids
- Wear-free keys react to the slightest touch

High-precision ball-bearing guide

Maximum sensitivity of the measuring system, long service life, and high loading capacity



Protection rating IP 64

Excellent protection against dust and splash water from all directions ensures optimum workshop compatibility at all times





Absolute measuring system The reference to the electric zero point is not lost when the device is switched off

Millimess 1002 / 1003 / 1010 / 2000 W / 2001 W Everything reliably under control



Order no.	Product	Measuring range		Display resolution		Details	List price	Offer price
		mm	μm	mm	μm		NOK	NOK
4335000	1002		± 25		0,5	Precision ball bearing of measuring spindle	7,580	4,900
4334000	1003		± 50		1	Precision ball bearing of measuring spindle	4,230	2,750
4334001	1003 XL		±130		2	Precision ball bearing of measuring spindle	4,230	2,750
4332000	1010		± 250		10	Precision ball bearing of measuring spindle	-3,150 -	1,990
4346700	2000 W	± 1		switchable 0.0001 0.01 mm/ .000005"0005"		Inductive measuring system, practical functions for static measuring tasks	-12,580 -	8,200
4346800	2001 W	± 1		switchable 0.0001 0.01 mm/ .000005"0005"		Inductive measuring system, practical func- tions for static and dynamic measuring tasks	-14,270 -	9,300

Millimar C 1202 Flexible evaluation and display anywhere

The Millimar C 1202 compact instrument is versatile and suitable for use with a variety of sensors.

The Millimar C 1202 represents the next generation of multichannel compact instruments for length metrology. Due to its sophisticated features such as the tilting easy-to-read display, clear menu navigation and flexible representation of measuring values, it offers maximum ergonomics and user-friendliness. Combine with an easy to change module from the N 1700 series to create just the right measuring instrument for your measuring task. Thanks to its wide range of functions, the Millimar C 1202 is extremely versatile. It can be used to tackle a multitude of measuring tasks, e.g. static and dynamic measurements as well as cone calculations. Moreover, depending on the module, measuring probes by other manufacturers may also be compatible, which will reduce your costs.

Tilting display

Measuring values can be read clearly and effortlessly from all viewing angles. The display also features a backlight.

Sturdy plastic housing

As the Millimar C 1202 is impervious to external influences, it is ideal for use in production.

Interchangeable modules

The Millimar C 1202 can be easily converted to handle different measuring tasks.



9

Different N 1700 modules can be combined with Millimar C 1202



Users can position the instrument on the table or fix it to the wall.

Millimar C 1200 / 1318 / P 2004 Smart and universal application



Order no.	Product	Numerical display	Resolution	Details	List price	Offer price
		μm	μm		NOK	NOK
5312012	Millimar C 1200 M	± 5000	0.1	High-resolution, high-contrast TFT color display	21,870	13,300
Order no.	Product	Measuring range	Measuring force	Details	List price	Offer price
Order no.	Product	Measuring range	Measuring force	Details	List price NOK	Offer price NOK
Order no. 5323010	Product P 2004 M			Details Inductive probe		

Millimar C 1202 / N 1702 / P 2004 / P 1512 / P 1530 Flexible evaluation and display anywhere



Order no. 5312025	Product Millimar C 1202	Numerical display μm ± 999 999.9	<mark>Resolution</mark> μm 0.01, 0.1, 1	Details High-resolution, high-contrast	List price NOK 17,930	Offer price NOK 11,400
Order no.	Product	Measuring range	Measuring force	TFT color display Details	List price	Offer price

Order no.	Product	Measuring range	Measuring force	Details	List price	Offer price
		mm	Ν		NOK	NOK
5331120	Millimar N 1702 M	± 2		Module for 2 inductive probes, Resolution 0.1 µm	- 8,280 -	4,900
5331125	Millimar N 1702 M-HR	± 0.2		Module for 2 inductive probes, Resolution 0.1 µm		10,600
5323010	P 2004 M	± 2	0.75	Inductive probe	- 6,200 -	3,750
5313180	1318	- 0.3 1	0.25 +/-0,05	Inductive lever probe	- 15,900 -	9,600
5331161	Millimar N 1702 VPP			Module for incremental sensors		4,700
5315081	P 1512 V	12	0.6 - 1.2	Incremental probe	- 15,490 -	9,800
5315311	P 1530 V	30	0.4 - 1	Incremental probe	-21,450 -	13,500

Digimar 817 CLT

Reaching great heights with maximum precision and flexibility



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4429600	817 CLT	0-350	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm		79,000
4429601	817 CLT	0 - 600	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm	- 130,100 -	87,000
4429602	817 CLT	0 - 1000	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm	- 198,000 -	125,000

Digimar 814 SR

Ideal for the workshop, robust and universally applicable.



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		NOK	NOK
4426100	814 SR	0 - 350	0.01	Digit height 12 mm, handwheel for positioning and measuring		8,700
4426101	814 SR	0 - 600	0.01	Digit height 12 mm, handwheel for positioning and measuring	-23,080-	14,900

Precimar SM 60 / SM 60-V Simple and robust, ideal for production and QA



Order no.	Product	Measuring range	Application range	Mount ø	Details	List price	Offer price
		mm	mm	mm		NOK	NOK
5357360	SM 60	25	0 - 60	8	Table size ø 60 mm	- 44,110 -	23,000
5357380	SM 60-V	25	0 - 60	8	Table size ø 60 mm, incl. pair of carbide anvils Ø 3.5 mm	35,000 -	24,500

Precimar ICM 100 IP



The powerful USB 3.0 camera and sturdy LED lighting guarantee that all display values are clearly legible. Even when the scale or numerical display of your testpiece are not exactly centered in the image, the system will read the displayed values perfectly.

Precimar ICM 100

One-handed operation

Using just one hand and no tools, you can move the camera and light source to the optimal height and position for your measurement: Fold down the lever, adjust the height continuously – done. Handling is easy and, thanks to spring-supported weight reduction, particularly comfortable and ergonomic.

5351010

Manual mode

Precimar IP 100

379,000

Precimar ICM 100 IP

Do you want to check your testpieces manually in individual cases? You can still do so with easy handwheel operation. In manual mode, the camera serves as a magnifying glass. Thanks to the enlarged live image, you can read the display values more easily, thus making manual work faster and more reliable.

Order no.	Product	Measuring range	Measuring uncertainty MPE _{E1}	Details	Offer price		
		mm / inch	μm		NOK		
5351010	Precimar ICM 100 IP	100 / 4	0.2 + L / 250	Incremental measuring system, USB 3.0 CMOS camera. PC, mouse, key- board, monitor, software and commissioning are not included in the price	379,000		
Upgrade kit accessories							
5351050	for Precimar Optimar 100 (5320005)			Price excludes commissioning	on request		
5351060	for Precimar ICM 100 (5351000)		51000)	Price excludes commissioning	on request		
5351070	for Precimar ICM 100 (5351005)			Price excludes commissioning	on request		

Universal & reliable

The Precimar ICM 100 IP based

on the tried-and-tested Precimar ICM 100 dial indicator test station

 also known as Optimar 100.
 This versatile, market-tested solution can be used for checking analog and digital dial indicators as well as dial comparators by a wide range of manufacturers.

It provides traceable measuring results conforming to standards in a measuring range of up to

100 mm.

MarSurf PS 10 Mobile measuring made easy

The MarSurf PS 10 is the ideal entry level instrument for surface metrology: Its extraordinarily simple and intuitive operation, along with numerous safety functions including the automatic cutoff, make the device as easy to control as a cellphone. Due to its minimal size, it is also perfect for location-independent measurements – vertical, horizontal and even overhead if necessary. And thanks to the removable drive unit, the MarSurf PS 10 can be used flexibly in production.

The measuring instrument boasts three order options for increased flexibility: with stylus tip 2 μ m, 5 μ m and also a variant with a transverse drive unit (MarSurf PS 10 C2).



Intuitive operation: As easy as using a smartphone with a rotatable display





- Error-free operation thanks to an integrated, removable roughness standard
- Automatic cutoff selection, ensuring that even non-specialists get the correct measuring results

other optional probes





Always at hand

The calibration standard stays in the instrument and can be checked at any time.

Extremely easy to operate with detailed profile display

The large 4.3" high-resolution and backlit TFT touch display allows intuitive operation and precise representation of the measuring profile.

OI S LINSIEN IVEN

Flexible use

small parts.

The removable drive unit, in conjunction with the optional handheld support, lends this instrument added versatility where space

is limited, e.g. in holes or when measuring

Perfect evaluation and documentation

Measuring records are automatically created in the instrument without the need for additional software.

^{up to} 500,000

measurements can be stored in the instrument

31

parameters same range of functions as a laboratory instrument



TFT touch display similar to a smartphone



measurements without power supply



Order no.	Product	Measuring range	Probe	Details	List price	Offer price
		μm			NOK	NOK
6910230	PS 10	350	Skidded probe system	Storage capacity for min. 3900 profiles, min. 500,000 results, min. 1500 PDF protocols, expandable with microSD card up to 32 GB	- 34,900-	25,900

MarSurf M 310 Brings added value for mobile roughness measurement

Are you used to using your smartphone to access your data anytime, wherever you are? That is exactly what Mahr's MarSurf M 310 provides you with: A versatile device for the mobile recording and evaluation of measuring data. Simple operation and a robust design make this Mahr product perfectly suited for use in production, where dirt and dust can clog the instrument and it is often users with little prior knowledge performing the quality control.

For all those who need more

The **MarSurf M 310** has the same functions as the PS 10 but has even more crucial added benefits for you:



Print directly, document easily

Measuring results in paper form? Sometimes still the fastest way! The mobile printer allows you to save data on thermal paper, which can then be added directly to the workpiece.

Preprogrammed measuring functions for immediate measuring success

A variety of measuring parameters can be defined, saved and then called up on the workpiece in the device settings. Additionally, it works using a barcode scanner, which simply connects to the MarSurf M 310. This allows even workers without expert knowledge or training to determine reliable roughness parameters.

Robot ready: Integrate instrument directly in the production line

The MarSurf M 310 and its interfaces can be directly integrated into your production lines, such as for measuring tasks on the robot arm. They control the measuring instrument remotely – conveniently from your computer, for example.

Status at a glance

Instrument status at a glance thanks to two easily visible status LEDs. Depending on the signal color, a measurement is underway, data is being transferred or an error has been detected. Standby mode shows the charging status.

Robust in every respect

Equipped for virtually any environment: The robust skidded probe system means that the measuring instrument is less sensitive to vibrations. The PHT probe is easy to clean due to its open skid.

Modern optics, perfect display

A high resolution, backlit 4.3" TFT display ensures precise display of your measuring results. It is oper-ated directly via the touchscreen - just as you are used to with your smartphone.

IATF compliant

The MarConnect duplex interface enables the transmission of a measuring equipment ID with each measurement. This makes measuring results traceable at any time.

RIC ISO 16610.21 0,8 mm

O MODE

ISO 21920 ready

Main Harsut M 310

At the turn of the year 2021/22, the new roughness standards DIN 21920-1 to 3 take effect. The MarSurf M 310 is compliant with these new standards.

Software with a success guarantee

With this measuring instrument, you can reliably determine roughness parameters even without expert knowledge or training due to intuitive software, clear menu structures and preprogrammed measuring functions.





Ver 5.0

Product Measuring range Offer price Order no. Probe Details List price NOK NOK μm 6910260 MarSurf 350 Skidded probe system Storage capacity for min. 3900 profiles, 1500 PDF 50,120 36,000 M 310 SET 2 µm probe tip protocols and 500,000 results, expandable with microSD card up to 32 GB 6910267 MarSurf 350 Skidded probe system Additionally with USB/Bluetooth printer and 49,600 39,000 M 310 SET docking station for direct printout of profiles, 2 µm probe tip ADC and MRC diagram and measurement results with printer

Detailed information on the products can be found at https://metrology.mahr.com/en-int/ All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in NOK plus VAT are valid from April 1, 2024 to May 31, 2024 Bluetooth*

MarSurf M 410

Simple, innovative, flexible – modern surface metrology to be used by hand

Mobile recording and evaluation of measuring data has never been this easy. The MarSurf M 410 is convenient and flexible to use – just a like a modern smartphone. It has a practical touch display, an integrated PDF memory, innovative accessories, and can transfer data via Bluetooth – all of which effectively simplify your workload.

Benefit from functions that only Mahr can offer you. In addition to the practical and efficient design and the flexibility this offers, the MarSurf M 410 also has an automatic filter setting by detecting the surface structure. This automatic contacting also guarantees the unmatched reliability of your measurements. The magnetic 3-point holder for the probe arm and the freely combinable accessories offer additional process security.

Possible to separate the display and probe system

Optionally, you can use the measuring instrument as a mini mobile measuring station, for example by simply attaching the display to the wall using the supplied pivoted docking station.

Advantages

- Increased efficiency thanks to large integrated memory: More than 500,000 measuring programs and 1,500 PDF reports, can be expanded by 32 GB (microSD)
- Skidless probes ensure that the roughness and waviness can be measured without an additional measuring station being required – determination of parameters R, W and P.
- · Safe measuring results thanks to automated cutoff option
- · Automatic zeroing ensures process and material safety
- IATF ready simply activate/deactivate in the menu by automatically transferring the item and serial number of the measuring instrument
- Free MarCom software to transfer data

Magnetic probe holder

Probe arms can be changed quickly without tools and with additional protection: The magnetic 3-point holder ensures that the probe will not be broken in the event of a collision; it will simply be released by the magnetic holder.

Intuitive operation via touch display

Easy to operate just like a smartphone so that no training or introduction to the operating functions is required – you can just get started.

Creation of PDFs directly on the device

Practical: The device creates a complete PDF file without the need for additional software or transfer to a computer. Information can be added to the PDF files directly on the device.

Wireless data transmission

Connect your measuring instrument to a PC via Bluetooth and transfer your data wirelessly to Excel or another software application, for example.



Importing information using a scanner

Simply start your measuring program by scanning a QR or barcode. You do not need to enter any profile information as your saved measuring programs are linked with a corresponding code.





Simple alignment of the

The inclination is easy to correct via the menu-driven, graphic

probe system

instructions.

Order no. Probe Details Offer price Product Measuring range List price NOK NOK μm 6910290 500 µm with probe arm length 45 mm Storage capacity for min. 3900 profiles, 1500 PDF 98,000 MarSurf 139,000 M 410 Set (±250 µm) bis1500 µm (±750 µm) protocols and 500,000 results, expandable with with probe arm length 135 mm microSD card up to 32 GB (increases the storage capacity by a factor of 320) 6910291 MarSurf 500 µm with probe arm length 45 mm Storage capacity for min. 3900 profiles, 1500 PDF 149,000 105,000 M 410 Set bis1500 µm (±750 µm) protocols and 500,000 results, expandable with (±250 µm) (incl. printer) with probe arm length 135 mm microSD card up to 32 GB (increases the storage capacity by a factor of 320)

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in NOK plus VAT are valid from April 1, 2024 to May 31, 2024

Spring Sale 2024 | 29

MarSurf CD 140 AG 11 Versatile with intelligent probe system

Mahr has launched a new contour measuring machine on the market – the MarSurf CD 140 AG 11. Its probe system has a measuring range of up to 70 mm and the stylus tips can be replaced quickly and without any tools – without having to recalibrate the system.

The new contour measuring machine MarSurf CD 140 AG 11 enables the user to complete fast and precise measurements. Its flexible workpiece holder makes it particularly easy to handle, while users are also convinced by its extreme versatility – it can also be used to measure roughness. The intelligent probe system and magnetic stylus tip holder ensure the process to replace stylus tips without any tools is the most straightforward process to date. Operators can also choose from a comprehensive range of clamps and workpiece holders. The new MarSurf CD 140 AG 11 can be used in a static position or directly at the location of the workpiece.



+

Advantages

- · Comprehensive contour measurement functions fast and simple
- Quick adjustment of the Z-axis with handles that are simple to operate
- · Replacement of the stylus tip without any tools
- Travel speed in the X-axis of up to 200 mm/s
- · Simple program creation or single measurement using MarWin
- Automatic evaluation, best adjustment of contours, CAD contour comparison, and a lot more
- Flexible support plate with 50 mm bore grid for KMG workpiece holder, amongst other
- Optionally expandable with option of roughness measurements (Rz >2 μ m)
- · Measurement with double stylus





Plug-in guide stops and a wide range of standardized clamping devices as well as workpiece holders enable flexible positioning of your testpiece.





Mahr GmbH Carl-Mahr-Straße 1 37073 Göttingen Germany

Reutlinger Straße 48 73728 Esslingen Germany

Phone: +49 551 7073 800 info@mahr.com www.mahr.com

Available from:



© **Mahr** GmbH We reserve the right to make changes to our products, especially due to technical improvements and further developments. All illustrations, numerical values, etc. are therefore subject to change. 3766349-EN-NOK | 03.2024