

22 P Portable Thickness Gages

Portable measurement of sheet materials and small parts



22P-15

Features

- Indicator built into gage frame for maximum ruggedness.
- Lift-lever for one-hand operation.
- Continuous reading dials with revolution counter for absolute measurement of thin materials, plastic films, a small parts.
- 6.3 mm/ .25" diameter, flat steel contacts.
- XLI Models (with μ Max μ m[®] XL Digital Indicator) can be Left/Right hand operated or front mounted and used with BA-26 Stand for bench applications.



XLI-22P-20 with XLI-20000 μ Max μ m XL Digital Indicator (front mounted) and BA-26 Stand (Stand not included)



XLI-22P-20 with XLI-20000 μ Max μ m XL Digital Indicator

Technical Data

Metric	Inch	Capacity	Throat Depth	Graduation
22P-10M	22P-11	0-2.54 mm/ 0-.10"	28.6 mm/ 1.13"	.002 mm/ .0001"
22P-15M	22P-15	0-12.70 mm/ 0-.50"	50 mm/ 2"	.01 mm/ .001"
22P-20M	22P-20	0-25 mm/ 0-1"	50 mm/ 2"	.01 mm/ .001"
XLI-22P-20		25 mm/ 0-1"	50 mm/ 2"	.001mm/ .00005" (Resolution)